

36" NEO-ANGLE Shower Ensembles

DURAWALL® Shower Walls, DURABASE® Shower Floors & STYLEMATE® Enclosures



The dramatic look of a premium-quality NEO-ANGLE shower ensemble from E.L. Mustee & Sons, Inc., is the proven way to transform any bathroom space into something very special.

Mustee's 36" NEO-ANGLE shower ensembles are created using a DURABASE® shower floor, DURAWALL® shower walls and a STYLEMATE® enclosure. The popular 36" NEO-ANGLE shower fits perfectly in most bathrooms to create a great shower space.

Features:

- High quality, molded-fiberglass construction provides years of service.
- DURAWALL® panels feature a sturdy, watertight tongue-and-groove design in addition to two large, molded-in shelves.
- Mounts direct-to-stud with mounting flanges hidden behind drywall or other wall treatment.
- STYLEMATE® enclosure with tempered safety glass, a continuous-pull handle and magnetic seal.
- DURABASE® fiberglass shower floors are strong, stable and feature a slip-resistant Starburst® floor surface design.
- All surfaces are mold/mildew resistant, easy to clean, with a deep-gloss finish.

Code Accepted:

Fiberglass Shower Ensembles meet or exceed performance requirements:

- American Society of Testing and Material (ASTM) — D 635, E 84 and E 162
- American National Standards Institute (ANSI) — Z 124.1.2 and Z 97.1
- IAPMO® as indicated 
- Warnock Hersey® as indicated 

Specifications


General: Furnish and install per plans, 36" NEO-ANGLE shower, manufactured by E.L. Mustee & Sons, Inc., consisting of:



DURAWALL® SHOWER WALL

Model	Color
736CWHT	White
736CBN	Bone

DURAWALL® Shower Wall — Model _____ shall be semi-gloss, 3-piece wall. Panels are molded fiberglass, using matched metal molds under extreme heat and pressure with a minimum uniform thickness of 125 mils and mount direct-to-studwalls. Include corner panel and two side panels with two molded-in shelves. Self-aligning panels using a tongue-and-groove connection. Shall meet ANSI Specification Z 124.1.2. Color _____ (White, Bone).




DURABASE® SHOWER FLOOR

Model	Color
3636CM	White
3636CBN	Bone

Center lines:
17½"x24⅝"x17½"

DURABASE® Shower Floor — Model _____ floor to be one-piece, molded fiberglass, made with matched metal molds. Surface to be slip-resistant Starburst® design that does not interfere with the flow of water. Size 36" x 36". Shoulder will be no less than 3" high or less than 1" wide. Tiling flange will extend not less than 1" higher than the threshold which provides an integral molded water barrier. Threshold will be not less than 4 ½" high. Molded-in drain and drain seal for installation of 2" iron DWV (Sch. 40) PVC or ABS sanitary drain pipe. Removable strainer. Shall meet ANSI Specification Z 124.1.2. Color _____ (White, Bone).



STYLEMATE® ENCLOSURE

Model	Finish/Type Glass
36.750	Chrome/Obscure
36.761	Chrome/Clear
36.762	Brushed Nickel/Clear
36.763	Oil-Rubbed Bronze/Clear

STYLEMATE® Enclosure — Model _____ with _____ (Chrome, Brushed Nickel, Oil-Rubbed Bronze) finish aluminum frame. Safety glass panels shall be _____ (Clear or Obscure) tempered glass. Side-wall jambs adjust ¾" for cut-of-plumb walls. Reversible pivot door with continuous-pull handle and magnetic seal. Door can be hung to open left or right. Shall meet ANSI Specification Z 97.1.

38" NEO-ANGLE Shower Ensembles

DURAWALL® Shower Walls, DURABASE® Shower Floors & STYLEMATE® Enclosures



The dramatic look of a premium-quality NEO-ANGLE shower ensemble from E.L. Mustee & Sons, Inc., is the proven way to transform any bathroom space into something very special.

Mustee's 38" NEO-ANGLE shower ensembles are created using a DURABASE® shower floor, DURAWALL® shower walls and a STYLEMATE® enclosure. The popular 38" NEO-ANGLE shower fits perfectly in most bathrooms to create a large shower space.

Features:

- High quality, molded-fiberglass construction provides years of service.
- DURAWALL® panels feature a sturdy, watertight tongue-and-groove design in addition to two large, molded-in shelves.
- Mounts direct-to-stud with mounting flanges hidden behind drywall or other wall treatment.
- STYLEMATE® enclosure with tempered safety glass, a continuous-pull handle and magnetic seal.
- DURABASE® fiberglass shower floors are strong, stable and feature a slip-resistant Starburst® floor surface design.
- All surfaces are mold/mildew resistant, easy to clean, with a deep-gloss finish.

Code Accepted:

Fiberglass Shower Ensembles meet or exceed performance requirements:

- American Society of Testing and Material (ASTM) — D 635, E 84 and E 162
- American National Standards Institute (ANSI) — Z 124.1.2 and Z 97.1
- IAPMO® as indicated 
- Warnock Hersey® as indicated 

Specifications

General: Furnish and install per plans, 38" NEO-ANGLE shower, manufactured by E.L. Mustee & Sons, Inc., consisting of:




DURAWALL® SHOWER WALL

Model	Color/Type Glass
738CWHT	White



DURAWALL® Shower Wall — Model 738C shall be semi-gloss, 3-piece wall. Panels are molded fiberglass, using matched metal molds under extreme heat and pressure with a minimum uniform thickness of 125 mils and mount direct-to-studwalls. Include corner panel and two side panels with two molded-in shelves. Self-aligning panels using a tongue-and-groove connection. Shall meet ANSI Specification Z 124.1.2. White color.




DURABASE® SHOWER FLOOR

Model	Color/Type Glass
3838CM	White

Center lines:
19 1/2" x 24 3/8" x 19 1/2"



DURABASE® Shower Floor — Model 3838CM floor to be one-piece, molded fiberglass, made with matched metal molds. Surface to be slip-resistant Starburst® design that does not interfere with the flow of water. Size 38" x 38". Shoulder will be no less than 3" high or less than 1" wide. Tiling flange will extend not less than 1" higher than the threshold which provides an integral molded water barrier. Threshold will be not less than 4 1/2" high. Molded-in drain and drain seal for installation of 2" iron DWV (Sch. 40) PVC or ABS sanitary drain pipe. Removable strainer. Shall meet ANSI Specification Z 124.1.2. White color.



STYLEMATE® ENCLOSURE

Model	Finish/Type Glass
38.750	Chrome/Obscure
38.760	Chrome/Clear w/Stripes
38.751	Chrome/Clear
38.752	Brushed Nickel/Clear
38.753	Oil-Rubbed Bronze/Clear

STYLEMATE® Enclosure — Model _____ with _____ (Chrome, Brushed Nickel, Oil-Rubbed Bronze) finish aluminum frame. Safety glass panels shall be _____ (Clear or Obscure) tempered glass. Side-wall jambs adjust 3/4" for out-of-plumb walls. Reversible pivot door with continuous-pull handle and magnetic seal. Door can be hung to open left or right. Shall meet ANSI Specification Z 97.1.

To reorder, specify ADV-496